

# PLUS-1

GENUINE EUROPEAN FOR AMERICAN THINKERS



**CLEARCOATS**  
**HARDENERS**  
**SOLVENTS**  
**AEROSOLS**  
**PRIMERS**  
**URETHANE**  
**BASECOATS**

	<b>PAGE</b>
<b>CLEARCOATS</b>	<b>3</b>
<b>CLEARCOATS</b>	<b>4</b>
<b>SOLVENTS</b>	<b>6</b>
<b>AEROSOLS</b>	<b>8</b>
<b>PRIMERS</b>	<b>10</b>
<b>URETHANE</b>	<b>12</b>
<b>BASECOATS</b>	<b>13</b>
<b>TDS</b>	<b>14</b>
<b>TDS</b>	<b>15</b>

**Distributed by: PBE Coatings Corporation**

[www.pbecoatings.com](http://www.pbecoatings.com)

Office: 713-239-2920 / 281-974-3151

Email: [sales@pbecoatings.com](mailto:sales@pbecoatings.com) / [info@pbecoatings.com](mailto:info@pbecoatings.com)

8251 Kempwood Drive

Houston - Texas 77055



## UHS-66 ULTRA GLOSS

High quality UHS acrylic Clearcoat and extremely easy to apply. It stands out for its great reflection and depth. Ideal for painting complete vehicles and parts with its fast catalyst. Very good overspray absorption at high temperatures with its extra slow catalyst. Mix ratio 2:1

ITEM No.	SIZE	DESCRIPTION
UHS-66	5 Liters	UHS Ultra Gloss Clearcoat 2:1
H66-65	2.5 Liters	UHS Activator for UHS66 Fast
H66-75	2.5 Liters	UHS Activator for UHS66 Medium
H66-85	2.5 Liters	UHS Activator for UHS66 Slow

## UHS-32 SPEED GLAMOUR

UHS SPEED Clearcoat manufactured with the latest generation resins. Designed to give you a superior combination of outstanding performance appearance and value Excellent gloss and DOI being dust free within 30 minutes it can be polished in three hours air dry Has excellent flow and leveling Great UV and chemical resistance It is compliant under current VOC legislation. Mix ratio 2:1



ITEM No.	SIZE	DESCRIPTION
UHS-32	5 Liters	UHS Speed Glamour Urethane Clearcoat 2:1
H32-60	2.5 Liters	UHS Speed Activator for UHS32 Fast
H32-75	2.5 Liters	UHS Speed Activator for UHS32 Medium
H32-85	2.5 Liters	UHS Speed Activator for UHS32 Slow



## UHS-30 XTREME GLAMOUR

High quality UHS acrylic varnish and extremely easy to apply. It stands out for its great reflection and depth. Ideal for painting complete vehicles and parts with its fast catalyst. Use exclusively with reducers. Very good overspray absorption at high temperatures with its extra slow catalyst. Mix ratio 4:1:1

ITEM No.	SIZE	DESCRIPTION
UHS-30	Gallon	Xtreme Glamour Clearcoat 4:1:1
H3021-75	1Liter	Xtreme Glamour Activator Standard
R3021-60	1Liter	Xtreme Glamour Reducer Fast
R3021-75	1Liter	Xtreme Glamour Reducer Medium
R3021-85	1Liter	Xtreme Glamour Reducer Slow

## UHS-57 PREMIUM

UHS Clearcoat. It requires no thinning, giving excellent build and protection. Great DOI. Excellent gloss retention and durability over basecoat system. Water or solvent may be used over panel spot or overall vehicle. Dust free on 90 minutes. Mix ratio 2:1



ITEM No.	SIZE	DESCRIPTION
UHS-57	5 Liters	UHS Premium Urethane Clearcoat 2:1
H57-60	2.5 Liters	UHS Activator for UHS57 Fast
H57-75	2.5 Liters	UHS Activator for UHS57 Medium
H57-85	2.5 Liters	UHS Activator for UHS57 Slow
H57-95	2.5 Liters	UHS Activator for UHS57 Extra Slow



ITEM No.	SIZE	DESCRIPTION
MS-41	5 Liters	MS Clearcoat High Gloss 2:1
H41-60	2.5 Liters	MS Activator for MS41 Fast
H41-75	2.5 Liters	MS Activator for MS41 Medium
H41-85	2.5 Liters	MS Activator for MS41 Slow
H41-95	2.5 Liters	MS Activator for MS41 Extra Slow

## MS-41 HIGH GLOSS

MS scratch resistance Clearcoat fast curing. Characterized by a magnificent acrylic shine. Mix ratio 2:1

## HS-77 CROMIX

High solid Clearcoat with extreme scratch resistance. Possibility of applying one and a half or two coats. Great durability with high gloss. Manufactured with highly resistant resins and Silica nanoparticles providing extreme scratch resistance. Mixing ratio 4:1+15% reducer



ITEM No.	SIZE	DESCRIPTION
HS-77	Gallon	HS Cromix Clearcoat 4:1
H77-60	Liter	HS Activator for HS77 1L Fast
H77-75	Liter	HS Activator for HS77 1L Medium
H77-85	Liter	HS Activator for HS77 1L Slow



## C1501 SUPER FAST CLEARCOAT

Is a two component Clearcoat specially designed repair. It gives fast air dry specially in cold ambient conditions, is compliant under the current legislation. Easy application and high hardness. Mix ratio 1:1

ITEM No.	SIZE	DESCRIPTION
C1501	2.5 Liter	Fast15 HS Clearcoat
C1501L	1Liter	Fast15 HS Clearcoat
H1560	2.5 Liter	Fast15 HS Activator
H15601L	1Liter	Fast15 HS Activator



## MCC-674 MATT CLEAR

100 % matt clear with high build is clear has the ability to have faster curing time without cloudiness and bursts Glossy 83%. Mix ratio 4:1

ITEM No.	SIZE	DESCRIPTION
MCC-674	Gallon	Matt Clear 4 Liters 4:1
HCC-675	1Liter	Matt Clear Activator 1 L
MCC-671	1Liter	Matt Clear 1 Liter 4:1
HCC-672	1/2 Pint	Matt Clear Activator 250ml



## SCC-754 SATIN CLEAR COAT

High urethane satin clear coat designed for air dry and forced dry environments. SCC-754 provide a uniform satin and reduced gloss appearance as found in custom hot rods and OEM satin finishes. Satin Clear Coat should not be final sanded or polished as it will damage the satin appearance.

ITEM No.	SIZE	DESCRIPTION
SCC-754	Gallon	Matt Clear 4 Liters 4:1
HCC-675	1Liter	Matt Clear Activator 1L



## AS-500 FISHEYE ELIMINATOR

Additive to eliminate fisheye contamination in 2K products.

ITEM No.	SIZE	DESCRIPTION
AS-500	0.5 Liter	Fish eye Eliminator

## D-610 WAX & GREASE REMOVER

A pre- paint panel wipe solution for removal of contaminants. Standard evaporation.



ITEM No.	SIZE	DESCRIPTION
D-610	5 Liter	Wax & Grease Remover



## PLASTIC ADHESION PROMOTER

Primer designed to ensure adhesion on plastics.

ITEM No.	SIZE	DESCRIPTION
PAP-1	1 Liter	Plastic Adhesion Promoter
PAP-4	4 Liter	Plastic Adhesion Promoter



## R-322 URETHANE REDUCER

Solvent with high diluting power designed for both nitrocellulosic products and 2k polyurethanes.

ITEM No.	SIZE	DESCRIPTION
R-322	1 Liter	Urethane Reducer Premium Blend

## PCB-1 COLOR BLENDING SOLVENT

Formulated with resins, solvents and special additives, to ensure a perfect integration in metallic and pearl bilayer colors.



ITEM No.	SIZE	DESCRIPTION
PCB-1	Liter	Color Blending Solvent



## T-1270 FLATTENING AGENT

A concentrated paste based on silicas and special additives designed to make opaque car body products. Depending on the percentage used, all the desired brightness level.

ITEM NO.	SIZE	DESCRIPTION
T-1270-1	1-Liter	Flattening Agent
T-1270-4	4-Liter	Flattening Agent

## URETHANE REDUCER

Good quality economical acrylic reducers.



ITEM No.	SIZE	DESCRIPTION
066315	5 Liter	Urethane Reducer Fast
066325	5 Liter	Urethane Reducer Standar
066345	5 Liter	Urethane Reducer Slow





## AEROSOLS

Sort selection aerosol products with high quality performance and durability.

ITEM No.	SIZE	DESCRIPTION
444-000	400ml	Plastic Adhesion Promoter
444-039	400ml	1k Primer Light Gray
444-100	400ml	1K Clearcoat
444-122	400ml	Bumper Texture Gray
444-199	400ml	Bumper Texture Black
444-333	400ml	Guide Coat

ITEM No.	SIZE	DESCRIPTION
444-771	400ml	Blending Solvent for Clear
444-772	400ml	Matt Black
444-775	400ml	Blending Solvent for Color
444-882	400ml	Satin Black
444-992	400ml	Gloss Black
444-999	400ml	Promoter ALL Sufaces

ITEM No.	SIZE	DESCRIPTION
444-401	400ml	1K Primer Filler Light Gray
444-402	400ml	1K Primer Filler Dark Gray
444-403	400ml	1K Primer Filler Black
444-404	400ml	1K Primer Filler White

ITEM No.	SIZE	DESCRIPTION
444-711	400ml	Wheel Aluminum
444-941	400ml	Wax & Grease Remover
444-671	400ml	1K Matt Clearcoat



## P18 2K DTM URETHANE PRIMER

UHS high-build primer with excellent filling properties. Adheres to sanded old paints and putties surfaces. No shrinkage, no edge markings, fast drying and very easy to sand.

ITEM NO.	SIZE	DESCRIPTION
P18-G	Gallon	2K DTM Urethane Primer Gray
P18-B	Gallon	2K DTM Urethane Primer Black
P18-W	Gallon	2K DTM Urethane Primer White
P18-R	Gallon	2K DTM Urethane Primer Red
H300	Liter	Activator Standard

ITEM NO.	SIZE	DESCRIPTION
P18-GLITER	Liter	2K DTM Urethane Primer Gray
P18-BLITER	Liter	2K DTM Urethane Primer Black
P18-WLITER	Liter	2K DTM Urethane Primer White
H300-250	1/2 Pint	Activator Standard 250cc

## P1220 LACQUER PRIMER

Extra fast dry primer made from the latest generation raw materials, it provides excellent adhesion and is easy to sand. Mix ratio 2:1 with reducer



ITEM NO.	SIZE	DESCRIPTION
P1220-G	Gallon	Lacquer Primer Gray
P1220-B	Gallon	Lacquer Primer Black
P1220-R	Gallon	Lacquer Primer Red
P1220-W	Gallon	Lacquer Primer White

ITEM No.	SIZE	DESCRIPTION
P1220-GLITER	Liter	Lacquer Primer Gray
P1220-BLITER	Liter	Lacquer Primer Black
P1220-RLITER	Liter	Lacquer Primer Red
P1220-WLITER	Liter	Lacquer Primer White



## EPOXY PRIMER

Primer made with epoxy resins and anticorrosive pigments. Excellent adhesion on metals. Great leveling and cannot be sanded wet & wet. Once dry it can be repainted with any finish.

ITEM NO.	SIZE	DESCRIPTION
P-EPX-4L	Gallon	Epoxy Primer Gray 4:1
E1125-1	Liter	Epoxy Primer Activator

ITEM NO.	SIZE	DESCRIPTION
P-EPX-1L	Liter	Epoxy Primer Gray 4:1
E1125-250ML	1/2 Pint	Epoxy Primer Activator 250ML

## ETCH-PRIMERS

This primer is manufactured with the highest quality components, it has a high adhesion on any ferric and non-ferric metal, free of rust. It has high resistance to corrosion. Suitable for total or partial repair.



ITEM No.	SIZE	DESCRIPTION
P-ETCH-1G	1 Litter	Self Etching Primer Gray
P-ETCH-1B	1 Litter	Self Etching Primer Black
P-ET1250-1	1 Litter	Self Etching Activator

ITEM No.	SIZE	DESCRIPTION
P-ETCH-4G	Gallon	Self Etching Primer Gray
P-ETCH-4B	Gallon	Self Etching Primer Black
P-ET1250-4	Gallon	Self Etching Activator





## ACY ACRYLIC URETHANE

**PLUS-1** pre-mixed single stage colors is a urethane resin base that provides excellent coverage and color formulation for automotive refinish applications.

ITEM No.	SIZE	DESCRIPTION
ACY-22	Gallon	Acrylic Urethane White
ACY-001	Liter	Acrylic Urethane Activator

## ACY ACRYLIC URETHANE

**PLUS-1** pre-mixed single stage colors is a urethane resin base that provides excellent coverage and color formulation for automotive refinish applications.











ITEM No.	SIZE	DESCRIPTION
ACY-99	Gallon	Acrylic Urethane Black
ACY-001	Liter	Acrylic Urethane Activator



















## BASE COATS










**PLUS-1** pre-mixed Basecoat colors provides excellent coverage and color formulation for automotive refinish applications.







ITEM No.	SIZE	DESCRIPTION
350BR	3.5L	Basecoat Paint Bright Red
350DB	3.5L	Basecoat Paint Deep Black
350SC	3.5L	Basecoat Paint Silver Coarse
350SF	3.5L	Basecoat Paint Silver Fine
350SM	3.5L	Basecoat Paint Silver Medium
350SW	3.5L	Basecoat Paint Snow White






	MIX RATIO	POT LIFE	APPLICATIO N VISCOSITY	SPRAY GUN	LAYERS	DRY TIME	FLASH TIME	POLISHING
PRODUCT								
CC1501	1:1 +0,7%	40min.	16-18" CF4 68°F	1,2 - 1,3mm	50-60 µc. 1/2 coat + 1 full coat	30' 68°F 4' 140°F	5 min flash off	Polishing 50m









	MIX RATIO	POT LIFE	APPLICATIO N VISCOSITY	SPRAY GUN	LAYERS	DRY TIME	FLASH TIME	POLISHING
PRODUCT								
UHS66	2:1 +5-10%	90 min 68°F	19-20" CF4 68°F	1,2 - 1,3mm	50-60 µc 1/2 coat + 1 full coat	3h 68°F 20' 140°F	15 min flash off	Polishing 3h
UHS32	2:1 +5-10%	3h 68°F	CF4 18-20"	1,2 - 1,3mm	2 cross coats 50-60 min.	25' 140°F 45' 68°F	Force dry 20' a 140°F / H805	Polishing 2h
UHS57	2:1 +5-10%	3h 68°F	CF4 18-20"	1,2 - 1,3mm	2 cross coats	Polish 3h	15 min flash off	Polishing 3h
MS41	2:1 +0- 10%	3h 68°F	CF4 17-19" 68°F	1,3 - 1,4mm	50-60 µc 2 full coats	Polish 6h	10/15 min flash off	30/140°F 8h 68°F

	MIX RATIO	POT LIFE	APPLICATIO N VISCOSITY	SPRAY GUN	LAYERS	DRY TIME	FLASH TIME	POLISHING
PRODUCT								
UHS77	4:1	90 min 68°F	CF4 16-18"	1,3 - 1,4mm	2 cross coats	2h 68°F 25' 140°F	10' flash off	Polishing 3h
UHS30	4:1:1 +10-15 %	3h 68°F	19-20" CF4 68°F	1,2 - 1,3mm	50-60 µc 1/2 coat + 1 full coat	3h 68°F 20' 140°F	15 min flash off	Polishing 3h
MCC674	4:1	90 min 68°F	CF4 18-20"	1,3 - 1,4mm	2 cross coats o 1 full coat + 1 dry coat	90' 68°F 20' 140°F	15 min flash off / 20 min before bake	NO

	MIX RATIO	POT LIFE	APPLICATIO N VISCOSITY	SPRAY GUN	LAYERS	DRY TIME	SANDING	FLASH TIME	INFRARED DRYING
<b>PRODUCT</b>									
P1880	4:1	1h. 68°F	CF4 70-80"	Ø1,6 - 1,8mm	100-150 2 coats	45' 68°F	2-3h. P400 P500	5-10 min flash off	12-15'

	APPLICATIO N VISCOSITY	SPRAY GUN	LAYERS	DRY TIME	INFRARED DRYING	SANDING
<b>PRODUCT</b>						
P1220	64"	30-35 %	1 - 3 coats 50-60 min	20' - 68°F	10-15'	P400

	MIX RATIO	APPLICATIO N VISCOSITY	SPRAY GUN	LAYERS	FLASH TIME
<b>PRODUCT</b>					
ETCH	1:1 0-15%	CF4 25"	Ø 1,2-1,4 mm	2-3 coats	45' before paint

	MIX RATIO	POT LIFE	APPLICATIO N VISCOSITY	SPRAY GUN	LAYERS	DRY TIME	FLASH TIME	BRUSH APPLICATIO N
<b>PRODUCT</b>								
P-EPX	4:1	24h.	CF4 25-35"	Ø1,6 - 1,8mm 10-15%	50-100 my	45'	15-30' 170°F/30 (Booth)	No diluted

# PLUS-1

Distributed by:



PBE COATINGS  
CORPORATION

PBE Coatings Corporation

[www.pbecoatings.com](http://www.pbecoatings.com)

Office: 713-239-2920 / 281-974-3151

Email: [sales@pbecoatings.com](mailto:sales@pbecoatings.com) / [info@pbecoatings.com](mailto:info@pbecoatings.com)

8251 Kempwood Drive

Houston - Texas 77055